



Contribution ID: 105

Type: **Poster**

A New Measuring Cell for Operando Neutron Diffraction on Li-Ion Battery Cathode Materials

Wednesday, 11 December 2019 15:40 (20 minutes)

The use of operando diffraction has taken a major step forward, in no small part due to the increase in flux at large scale facilities such as synchrotrons and neutron spallation sources. While the X-rays are absorbed by the battery casing which necessitates special cells with windows, neutrons have a penetration depth large enough to probe the entirety of cell. This has allowed measurements directly on commercial batteries, giving unique insights into the evolution of cell parameters and composition of the cathode and anode phase.

When measuring on commercial cells, contributions from all parts of the cell are observed which complicates the analysis of the diffraction data. A desire also exists to measure on non-commercial electrode materials prepared in the lab. Thus, there exists an incentive to develop a measuring cell which allows easy measurement on a variety of different cathode materials, either commercial or synthesized.

In this work, we present a new operando neutron diffraction battery cell, especially designed for the new beamline ErwiN at the FRM-2 research reactor outside of Munich, Germany. The cell uses a Zr/Ti-alloy with negligible scattering strength to eliminate contributions from the casing. We present data on the commercial cathode materials LiFePO_4 and $\text{LiNi}_{1/3}\text{Mn}_{1/3}\text{Co}_{1/3}\text{O}_2$ to demonstrate the capabilities of the cell, as well as on the non-commercial cathode material $\text{LiNi}_{0.5}\text{Mn}_{1.5}\text{O}_4$.

Primary authors: SØRENSEN, Daniel (MLZ); HEERE, Michael; SENYSHYN, Anatoliy

Presenter: SØRENSEN, Daniel (MLZ)

Session Classification: Poster session

Track Classification: Materials Science